Amendments to the Specification:

36

A 1/06

The paragraph beginning at Page 4, please amend line 17 as follows:

Figs. 17A, 17B and 17C show side and rear perspective views of the PCT support of Fig. 16.;

the adhesive material may be deposited on either side of the row of apertures to provide stability for the mounting arrangement. The adhesive material may be a curable resin.

An embodiment of a printhead module that incorporates features of the present invention is now described by way of example with reference to the accompanying drawings, as is an embodiment of a printhead assembly that incorporates the printhead module.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings:

5

- Fig. 1 shows a perspective view of a printhead assembly in accordance with an embodiment of the present invention;
 - Fig. 2 shows the opposite side of the printhead assembly of Fig. 1;
 - Fig. 3 shows a sectional view of the printhead assembly of Fig. 1;
 - Fig. 4A illustrates a portion of a printhead module that is incorporated in the printhead assembly of Fig. 1;
- Fig. 4B illustrates a lid portion of the printhead module of Fig. 4A;
 - Fig. 5A shows a top view of a printhead tile that forms a portion of the printhead module of Fig. 4A;
 - Fig. 5B shows a bottom view of the printhead tile of Fig. 5A;
 - Fig. 6 illustrates electrical connectors for printhead integrated circuits that are mounted to the printhead tiles as shown in Fig. 5A;
- Fig. 7 illustrates a connection that is made between the printhead module of Fig.:4A and the underside of the printhead tile of Figs. 5A and 5B;
 - Fig. 8 illustrates a "female" end portion of the printhead module of Fig. 4A;
 - Fig. 9 illustrates a "male" end portion of the printhead module of Fig. 4A;
 - Fig. 10 illustrates a fluid delivery connector for the male end portion of Fig. 9;
- Fig. 11 illustrates a fluid delivery connector for the female end portion of Fig. 8;
 - Fig. 12 illustrates the fluid delivery connector of Figs. 10 or 11 connected to fluid delivery tubes;
 - Fig. 13 illustrates a tubular portion arrangement of the fluid delivery connectors of Figs. 10 and 11;
 - Fig. 14A illustrates a capping member for the female and male end portions of Figs. 8 and 9;
 - Fig. 14B illustrates the capping member of Fig. 14A applied to the printhead module of Fig. 4A;
- Fig. 15A shows a sectional (skeletal) view of a support frame of a casing of the printhead assembly of Fig. 1;
 - Figs. 15B and 15C show perspective views of the support frame of Fig. 15A in upward and downward orientations, respectively;
- Fig. 16 illustrates a printed circuit board (PCB) support that forms a portion of the printhead assembly of Fig. 1;
 - Figs. 17A, 17B and 17C show side and rear perspective views of the PCB support of Fig. 16;
 - Fig. 18A illustrates circuit components carried by a PCB supported by the PCB support of Fig. 16;
 - Fig. 18B shows an opposite side perspective view of the PCB and the circuit components of Fig. 18A;